

- Product-type:**
High Pressure compact laminate reference NATURCLAD-W F (Thickness: 8 - 22 mm)
- Name & contact address of the manufacturer:**
PARKLEX PRODEMA INT, SLU
Barrio San Miguel nº 9
20250 Legorreta – Gipuzkoa – Spain
- Intended use of the construction product:**
As external finishes in walls or ceilings, subject to reaction to fire regulations.
- System of assessment and verification of the constancy of performance:** 1
- Notified body:**
 - Tecnalía R&I Certificación NB 1239
 - Evaluation of the Factory Production Control
 - Reaction to fire for initial type testing
 - System 1
 - Certificate of constancy of performance of the product N° 1239/CPR/0801006 dated April 7, 2012
- Declared performance:**

Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B-s1;d0	EN 438-7:2005
Resistance to fire	NPD	
Water vapour permeability		
Wet cup	110	
Dry cup	250	
Resistance to fixings		
8 mm thickness	3.000 N	
≥ 10 mm thickness	4.000 N	
Direct airborne sound insulation	NPD	
Bonding Strength	NPD ¹	
Flexural tensile strength	PASS	
Thermal conductivity	0,22 w / m * k	
Content of pentachlorophenol	NPD ¹	
Release of formaldehyde	NPD ²	
Sound absorption	NPD ²	
Thermal shock resistance	PASS	
Durability: Resistance to wet conditions	PASS	
Durability: Density	PASS	

¹ Applicable only to HPL composite panels

² Applicable only to panels intended for internal use

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Santiago Bastida (R&D Manager).

Signature:



PARKLEX PRODEMA

Place and date of issue:

Legorreta, the 3rd of June 2022

PARKLEX PRODEMA INT, SLU

Barrio San Miguel nº9 – 20250 Legorreta – Gipuzkoa – Spain

[t] +34 943 80 70 00 – parklexprodema@parklexprodema.com

www.parklexprodema.com